Maintenance Free Motorcycle Batteries

WP14B-4

Specifications

Nominal Voltage(V)

12V

Nominal Capacity

10 hour rate	(1.2A	to	10.50V)	12Ah
5 hour rate	(2.04A	to	10.20V)	10.2Ah
1 C	(12A	to	9.60V)	5.4Ah
3 C	(36A	to	9.60V)	4.2Ah

Weight

Approx. 4.86kg(10.69Lbs.)

Internal Resistance (at 1KHz)

Approx. 8 mΩ

Cold Cranking Amperes (-17.8℃)

185A

High rate discharge characteristics (-10℃)

Discharge current (A)	100A
Duration (min)	2.2min
5 second voltage (V)	9.6V

Operating Temperature Range

Charge	-15℃(5℉)	to	40℃(104℉)
Discharge	-15℃(5℉)	to	50℃(122℉)
Storage	-15℃(5℉)	to	40℃(104℉)

Charge Retention (shelf life) at 20℃(68℉)

1 month	92%
3 month	90%
6 month	80%

Case Material

ABS UL94 HB

Terminal Shape

Front	Side	Top
		

Dimensions

Length (L)	$150\pm^{2}_{1}(5.91\pm^{0.08}_{0.04})$
Width (W)	$69\pm^{2}_{1}(2.72\pm^{0.08}_{0.04})$
Height (H)	$145\pm^{2}_{1}(5.71\pm^{0.08}_{0.04})$
Overall Height (HT)	$145\pm^{2}_{1}(5.71\pm^{0.08}_{0.04})$

mm(inch)





290318-1B

廣隆光電科技股份有限公司
KUNG LONG BATTERIES INDUSTRIAL CO., LTD.

Head Quarter Service TEL: +886-49-2254-777 FAX: +886-49-2255-139 E-mail: sales@mail.klb.com.tw
USA Customer Service TEL: +1-949-328-7936 FAX: +1-949-266-9917 E-mail: sales@kunglong.com
Vietnam Customer Service TEL: +84-272-3779666 FAX: +84-272-3779476 E-mail: sales@mail.klb.com.tw

Contents in this data sheet are subject to change for improvement without prior notice to users. For clarifications and updated information, please contact us.